

## High-performance greases



### Greases

Product	Base oil	Thickener	NLGI-grade	Viscosity at 40°C	Viscosity at 100°C	Service temperature range in°C	Available in:
Fomlube AR 555	PFPE	PTFE	2	345	33	240	Worldwide
Fomlube GRM 30	PFPE	PTFE	2	159	45	170	Worldwide
Fomlube GRM 60	PFPE	PTFE	2	310	86	190	Worldwide
Fomlube OT20	PFPE	PTFE	2	15	3.2	45	Worldwide
Fomlube OX HP	PFPE	Talc	2	1300 (at 20°C)	-	200	Worldwide
Fomlube RT 15	PFPE	PTFE	2	345	33	230	Worldwide
Fomlube UT 18	PFPE	PTFE	2	147	16	220	Worldwide
Fomlube VAC 3	PFPE	PTFE	3			230	Worldwide
Fomlube YNX	PFPE	Talc	2	80	10	190	Worldwide
Fomlube ZLHT	PFPE	-	2	92	28	120	Worldwide
Fomlube ZNF	PFPE	PTFE	3	157	49	160	Worldwide
Beruglide L	PFPE	PTFE	1-2	160	16	150	NL & BE
Berulub ND-fluid 160	PFPE	-	-	160	16	160	NL & BE
Berulub FK 164-2 UV	PFPE	PTFE	2	150	45	190	NL & BE
Berulub FK 164 Dispersion OZF 1-10	PFPE	-	-	150	-	170	NL & BE
Berulub FK 164 Dispersion OZF 0,5-20	PFPE	-	-	325	-	210	NL & BE
Berulub VPT 54-2	PFPE	PTFE	2	210	20	200	NL & BE
Berulub ND- dispersion 10	PFPE	-	-	325	20	210	NL & BE
IKV fluor MPA 2H	PFPE	PTFE + AC	2	500	-	230	NL & BE
IKV TRIBOFLON TXN 702	PFPE	TALC	2	-	-	200	NL & BE
IKV TRIBOFLON MYA 502 FG	PFPE	PTFE	2	510	47	255	NL & BE
ZAROX DMB 30	PFPE?	PTFE + AC	0	32	7.8	90	NL & BE
IKV FLUOR DML 2	PFPE	PTFE + AC	2	200	31	230	NL & BE
ZAROX DMA 212	PFPE	PTFE + AC	2	210	43.4	140	NL & BE
ZAROX DXA 162	PFPE	PTFE + AC	2	160	45	140	NL & BE